



RECTORSEAL

A CSW Industrials Company

Introducing Metacaulk 835+ **NEW!** **spray** grade firestop.



◀ Cures to a flexible water/rain resistant seal in 1 hour.

metacaulk®

835+^{SPRAY}

ELASTOMERIC

SILICONE FIRESTOP

- Weather/chemical resistant
- Non-sag • Flexible cure • Spray grade

Metacaulk® 835+ Spray is an elastomeric silicone based firestop sealant now available in spray grade.

- Prevents the spread of flames, smoke, hot gases and water through joint openings.
- Suitable for areas of significant movement
- Can be applied to horizontal and vertical surfaces
- Excellent moisture resistance
- Interior and exterior application
- Application temperature -20°F to 120°F
- Excellent freeze-thaw
- Meets Type S, Grade P, Class 25, Use NT, M, G, A, O

APPLICATIONS • Wall to floor transition joints • Wall to wall & floor to floor control joints • Curtain wall joints



Metacaulk 835+ Spray joins our line of 835+ silicone based caulks.



TESTED TO ASTM E1966 (UL 2079)

Sound Transmission Class (**STC**) 55 - The test was performed in accordance with ASTM E90, Standard Test Method for Laboratory Measurement of Airborne Sound Transmission Loss of Building Partitions and Elements.

TESTÉ SELON ASTM E1966 (UL 2079)

Indice de transmission du son (ITS) 55
L'essai a été réalisé conformément à la norme ASTM E 90, Méthode d'essai normalisée pour mesures en laboratoire des pertes de transmission des bruits aériens des cloisons de bâtiment.

RECTORSEAL, LLC
METACALK 835+ SPRAY



Intertek
Control No. 5009113

CERTIFIED TO:
UL 2079, ASTM E2307,
ASTM E1399, ASTM E1966

Refer to the Intertek
Directory of Building Products
(<https://directory.intertek.com>)
for detailed information.

www.metacaulk.com/mc835

NEW!

Metacaulk® 835+

Spray - Elastomeric, silicone firestop mastic

Code	Description	Qty.
66295	5 gal. spray grade	1



FEATURES

- Exterior / Interior use
- Weather/chemical resistant
- Excellent moisture resistance
- Tested to ASTM E1966 (UL 2079), ASTM E2307 and ASTM E1399 - Meets Type S, Grade P, Class 25, Use NT, M, G, A, O
- STC rating 55
- 18 month shelf life
- Color: Gray

APPLICATION • Used in systems where dynamic movement is expected

- Resistant to chemical exposure
- Forms a water/rain resistant seal after 1 hour

RECOMMENDED FOR

- Wall to floor transition joints
- Wall to wall control joints
- Floor to floor control joints
- Curtain wall joints



Metacaulk® 835+

Caulk - Elastomeric, silicone firestop sealant

Code	Description	Qty.
66645	10.15 oz. cartridge	12
66019	5 gal. caulk grade	1
66300	20.2 oz caulk grade	12
66301	20.2 oz self-leveling	12



FEATURES

- Exterior / Interior use
- Weather/chemical resistant
- Excellent moisture resistance
- Tested in accordance with ASTM E814 (UL 1479), ASTM E1966 (UL 2079), ASTM E84
- STC rating 55
- Meets ASTM C920, Type S, Grade NS, Class 25, Use NT, M, G, A, O (For SL- ASTM C920, Type S, Grade SL, Class 25, Use NT, M, G, A, O)
- 2 year shelf life
- Color: Gray

APPLICATION • Used in systems where dynamic movement is expected

- Resistant to chemical exposure

RECOMMENDED FOR

- Cable and cable trays • EMT
- Insulated and uninsulated steel pipe • Construction and control joints • Interior expansion joints

