metacaulk_®



Cast-In-Place Device Firestop for through floor penetration.





METACAULK® CAST-IN-PLACE DEVICE


Cast-In-Place Device

Firestop for through floor penetration.

Code	Cast-in-Place Device	Qty.
67202	2-inch device (8-in. height)	12
67203	3-inch device (8-in. height)	12
67204	4-inch device (8-in. height)	12
67206	6-inch device (8-in. height)	6
Code	Height Extension	Qty.
67232	4-in. extension for 2-in. device	6
67233	4-in. extension for 3-in. device	6
67234	4-in. extension for 4-in. device	6
67236	4-in. extension for 6-in. device	6
Code	Deck Adapter Kit	Qty.
67222	2-inch adapter & 4-in. extension	6
67223	3-inch adapter & 4-in. extension	6
67224	4-inch adapter & 4-in. extension	6
67226	6-inch adapter & 4-in. extension	6

APPLICATION • Single component Cast-In-Place device, approved for use with a multitude of penetrating items. Will prevent the spread of fire from through-penetration services in concrete floors • Installs prior to concrete pour. • Casts directly into the concrete to form an embedded intumescent service supply.

RECOMMENDED FOR • Combustible plastic/metal pipe, power & telephone cable floor penetrations in multi-floor construction. • Installs using both temporary wood or metal forms.







CID Alignment connectors allow tight placement of multiple penetrations.



FEATURES

- Integral intumescent firestop
- UL Classified systems up to 3 hrs
- Eliminates drilling of concrete
- Reduces labor time
- Tested in accordance with ASTM E814 (UL 1479)
- Assembled in the USA

